V4-10.15



Assembly Instructions



(W x D x H) 0.90m x 0.90m x 0.45m Product Name: Aquatic Planter

Pressure Treated products should not be treated with any other products for the first month.

PLEASE KEEP THESE INSTRUCTIONS

Aquatic Planter Assembly Instructions

Requires 2 person assembly.

Tools required: Corded / Cordless Drill, Pozi-drive Bit / Screwdriver, 3mm Drill Bit required in order for you to drill all screw holes before construction.

Aquatic Planter Pack List			
Item	Description	Quantity	
А	Panel	2	
В	Panel	2	
С	Capping Trim	4	
	Liner	1	
	Base – Optional Extra	1	

Fixings			
	60 mm Screws	32	
	70mm Screws – for Base Optional Extra	8	



Please take a few moments to check all pack contents listed.

Assembly requires 2 persons.

Tools required: Corded / Cordless Drill, Pozi-drive Bit / Screwdriver, 3mm Drill Bit required in order for you to drill all screw holes before construction.

- 1. Interlock Panels A with Panels B (Figs.1a & 1b) to form a square planter.
- 2. Secure in position using 8no Screws 2no per internal corner (Fig.2a) and 16no screws 4no per external corner (Fig.2b).

Planter Base – Optional Extra


- 3. Invert the planter and place the base as shown in Fig.3a. Fix in position using 8no 70mm Screws 2no per bearer (Fig.3b).
- 4. Place Liner into planter ensuring edges of liner are flush with outside edge of planter. Position Capping Trim C, ensuring internal face is flush with planter body and rounded corner outermost. Fix in position as shown in Fig.4a using 2no Screws.

Similarly fix remaining capping trims as shown (circled) in Fig.4b.




2a





2b



3a



Planter Base Optional Extra







4b



www.zest4leisure.co.uk